printf() – Debugging in Style

www.doralp.../printf_debugging

The Only Debugger That Never Lies
(Unless You Messed Up the Format String,

By Nick Doralp

The Only Debugger That Never Lies

(Unless You Messed Up the Format String, In Which Case It Will Lie Like a Politician on Fire, Douse Itself in Gasoline, and Blame the Compiler)

By Nick Doralp
MoN, PMP, CISA, EDP, ECP, EDI (ret),
PhD in Semicolon Trauma
High Priest of the Order of the Terminal Owl

website: https://www.doralp.ca
Email: nick@doralp.ca

"WHOOOOOOOSE bug is it anyway?" — The Great Hootini

Creative Commons Attribution 4.0 International (CC BY 4.0)

First Edition – October 2025 – ISBN: 978-1-4920-DEAD-BEEF
Printed on recycled core dumps and the tears of junior devs

www.doralp.ca/printf_debugging

printf() – Debugging in Style
© 2025 Nick Doralp

This work is licensed under Creative Commons Attribution 4.0 International (CC BY 4.0)



You are free to:
- Share — copy and redistribute
- Adapt — remix, transform, and build upon

As long as you give appropriate credit.
Full license: https://creativecommons.org/licenses/by/4.0/

Warning!

Reading this book may cause:

- Spontaneous fflush(stdout);
- Terminal worship
- Fear of newlines
- The urge to grep your dreams
- Sudden outbursts of “IT WORKS ON MY MACHINE!”
- Uncontrollable hooting

Why did the owl become a debugger?

Because it was a night owl — and the bugs only come out after dark.

www.doralp.ca/printf_debugging

Dedication

To the programmer who spent an entire afternoon staring at a single line of code,
only to realize they forgot a semicolon.

You are seen. You are loved. You are one `printf("I HATE MY LIFE\n");` away from salvation.

(Also to my dog, **Zeus,** who once fixed a race condition by sitting on the keyboard and typing `;`. True story. The owl was watching. The owl always watches.)

www.doralp.ca/printf_debugging

“printf() Oath” for New Devs

> *“I swear by the stack and the heap, by the ghost of Dennis Ritchie, and by the eternal gaze of the Terminal Owl, that I will never trust a debugger again. I will print. I will flush. I will blame Nick. So help me C.”*

Print it and sign in blood (or Red Bull or Jack Daniels).

www.doraiq.ca/printf_debugging

Foreword

By S. B. Glitch (CTO of Almost-Working Systems, Retired and Slightly Traumatized)

“I once saw Nick debug a kernel panic with a printf and a paperclip. The paperclip was for moral support. The owl was for moral judgment.”

When Nick told me he was writing a book, my first response was: “Nick, you’re not allowed to write a book about the one thing you actually do well.”
My second response was a frantic series of emails demanding that he dedicate the entire final chapter to apologizing for every time he used his cursed printf() method to find a bug I couldn’t. He declined both. The owl hooted in disapproval.

I have known Nick since 1975—that is not a typo—when he was coding on a machine that required less electricity to run than his morning coffee machine does now. He has always been a genius, and he has always been stubborn.

Nick is the kind of programmer who refuses to use a modern debugger because he believes that if the IDE is going to crash, it should at least do him the courtesy of taking the whole operating system with it. His method—and let’s be honest, it is a method—is

www.dorian.ca/printf_debugging

simply to carpet-bomb the codebase with statements like printf("VAL_X: %d\n", val_x); until the console output looks less like a log and more like a ransom note.

And the infuriating thing? It works.

While the rest of us are carefully setting conditional breakpoints, analyzing memory dumps, and respecting the separation of concerns, Nick is running circles around us armed with nothing but a keyboard, an overwhelming sense of self-confidence, and a command that literally means “print formatted.” The owl nods. The owl approves.

I tried to stop him. I really did. I spent ten years integrating a state-of-the-art logging framework that could pipe output to a remote server, handle rotation, and compress files into proprietary binary chunks. Nick just compiled his C code, ran it, and typed | grep "WTF". He found the bug in thirty seconds.

I hate this book. I hate that it will validate his approach. But if you are pressed for time, short on patience, and utterly committed to finding that one logic error buried three nested loops deep, this book is your last resort.

May your format strings always match your data types.
May your newlines flush.
And may you never, ever, forget the semicolon.

— S. B. Glitch

www.debrain.ca/printf_debugging

“Still trying to comment out all of Nick’s debug statements from a 20-year-old codebase. The owl is still watching.” - anonymous

Foreword from the Owl

“I have watched you since 1974. You type. You crash. You printf(). You cry. I do not blink. I do not forgive. But I approve.”

> ***— The Terminal Owl, High Priest of the Night Shift***

www.doraln.ca/printf_debugging

Author Bio: Nick Doralp (The printf() Whisperer)


WANTED
DEAD OR ALIVE
Alias: "THE ALL-SEEING EYE"
Crimes: Using: Using printff excessiny excessive during dring debugging.
Reward: Eternal admiration and a
Eternal admiration and a really nice 2 socks.

Nick Doralp is a figure shrouded in mystery and the faint scent of stale coffee or Jack Daniels. He emerged from the depths of a mainframe terminal in the mid 1970s and has been writing software—and fixing the terrifying mistakes of others—ever since.

He holds a Ph.D. in Applied Console Literacy from the University of Broken Pointers, and his groundbreaking thesis, “The Semi-Colon: A Post-Mortem Analysis,” is still widely ignored by students today. The owl, however, keeps a copy under its wing.

Doralp is best known for his belief that any problem that takes more than three hours to debug can be solved in three minutes by strategically placing a printf() statement containing his favorite phrase: “I AM HERE, YOU FOOL.” He communicates solely through cryptic commit messages and occasionally appears at programming conferences wearing a t-shirt that simply reads: “IT WORKS ON MY MACHINE.” The owl wears the same shirt. In owl size.

www.doralp.cs/printf_debugging

He currently resides somewhere between the stack and the heap, happily avoiding debuggers and IDEs. The owl perches on his monitor and hoots in binary.

www.doralp.ca/printf_debugging

Table of Contents

Warning! **4**
“printf() Oath” for New Devs 6
Foreword **7**
Foreword from the Owl 9
Author Bio: Nick Doralp (The printf() Whisperer) **10**
Table of Contents **12**
Part I: The Call to Print **15**
Chapter 1: The Initial Despair 16
1.1 A Segfault Walks Into a Bar 16
1.2 When the Debugger Fails 16
1.3 The Emergency Protocol 17
Chapter 2: Variables: The Truth and Nothing But the Truth 18
2.1 The Format String Inquisition 18
2.2 The Double Life of Floating-Point Numbers 18
Chapter 3: Styling the Output 20
3.1 ANSI Escape Codes 20
3.2 The Art of Indentation 21
3.3 The Header/Footer Method 22
Part II: Advanced Printing and The Cult of Nick Doralp **23**
Chapter 4: The Existential Horror of the Missing \n 24
Humorous Debug Statement Example 27
Chapter 5: Logging Architectures 28
5.1 Creating a Debug-Level Macro 29
5.2 The Conditional Print 30
5.3 The Global Boolean 32
Chapter 6: printf() Beyond C 34

www.doralp.ca/printf_debugging

6.1 Python’s print() 34
6.2 Java’s System.out.println 35
6.3 Shell Scripts and echo 35
Chapter 7: The Art of The Defensive Print Statement 37
7.1 The “I Swear I Fixed This” Variable Guard: 37
7.2 The Passive-Aggressive Log Message: 37
7.3 The Self-Destructing Debug Block: 38
Chapter 8: The Debugger's Ethical Dilemma: Printing PII 39
8.1 The User's Full Name: 39
8.2 The Unmasked Password: 39
8.3 The Clean-Up Protocol: 39
Chapter 9: The Zen of The Missing Output 40
9.1 Buffering: 40
9.2 The Primal Scream: 40
9.3 The fflush(stdout); Confession: 40
Part III: printf() in the Wild: Collaboration and Abuse 41
Chapter 10: The Collaborative Log Disaster 42
10.1 The Log Race Condition: 42
10.2 Debugging by Committee: 42
10.3 The Debug Log Blackout: 43
Chapter 11: The Dark Art of printf() Abuse 44
11.1 Printing Entire ASCII Art Banners: 44
11.2 The Database Query Dump: 44
11.3 printf() as an Instrumentation Tool: 44
Chapter 12: Legacy Logs: The Archaeological Dig 45
12.1 The Time Capsule Print: 45
12.2 The Profanity Filter: 45
12.3 The "TODO: Delete Me" Printout: 45

www.debugpoint.com/printf_debugging

"Hall of Shame" 46
Appendix A: The printf() Tarot: 78 Cards to Divine Your Bugs 47
Appendix B: printf() Ouija Board 48
Appendix C: printf() Mad Libs 49
⚠️ Errata and Known Issues (The "Wait, How Did That Pass QA?" Page) 51
1. The Missing Semicolon Incident (First Printing Only) 51
2. The Color-Blind Debugger 53
3. Pointer Arithmetic Paradox 54
4. The Self-Referential Bug 55
📚 Glossary of Terms 56
Essential Vocabulary for the Unrepentant Debugger 56
Disclaimer 60
Index 63
"You Shouldn't Be Here" 68

www.doralp.ca/printf_debugging

Part I: The Call to Print

“If your code doesn't compile, at least make it entertaining.”

— Nick Doralp, probably drunk on bourbon, hubris, and the blood of a thousand segfaults

www.doralp.ca/print-debugging

Chapter 1: The Initial Despair

1.1 A Segfault Walks Into a Bar

The Anatomy of a Bad Day

You're three coffees deep, the deadline is breathing down your neck like a dragon with halitosis, and your program just dereferenced NULL in front of the entire team. The core dump is so fresh it still has that new-corpse smell. You stare at the terminal the way a deer stares at an oncoming Tesla—wide-eyed, frozen, secretly hoping the autopilot will swerve. Spoiler: it won't. The only thing crashing faster than your code is your will to live. Welcome to Tuesday.

1.2 When the Debugger Fails

A Love Story That Ended in Tears

You and `gdb` were perfect together. You whispered `break main`, it whispered back `Breakpoint 1`. You said `run`, it said `Starting program…` and your heart fluttered. Then one day it just… stopped. "Cannot access memory at address 0x0." That's debugger for "It's not you, it's segfault." You tried `valgrind`, but it was just a

www.doralp.camp/ft_debugging

rebound—too slow, too chatty, kept pointing out leaks you didn't even know you had. Heartbroken, you closed the lid, opened `vim`, and did what any sane engineer does in a crisis: you typed `printf("still alive\n");` and prayed to the ghost of Dennis Ritchie.

1.3 The Emergency Protocol

Tossing in the First printf("Got here!");

This is not a drill. Red alert. You slap a `printf("Got here!");` at line 42 like it's a nicotine patch on a chain-smoker. Compile. Run. Silence. Okay, we never get here. Move it to line 38. Compile. Run. "Got here!" Victory screech. You are now 1/1,000,000th closer to enlightenment. Add another: `printf("And here! x=%d\n", x);`. Compile. Run. "`And here! x=42`". The variable is 42. You are one step away from achieving nirvana or realizing the bug is in the *next* line. Either way, the printf's are breeding now—little digital breadcrumbs leading you through the dark forest of spaghetti. Hansel and Gretel wish they had your version control.

www.oldmanscript_debugging

Chapter 2: Variables: The Truth and Nothing But the Truth

2.1 The Format String Inquisition

How to Match Your %d to Your int

Picture this: you `printf("Score: %d\n", player.health);` but `health` is a `uint64_t` because *of course* your orc can have 18 quintillion HP. The terminal responds by vomiting the next 4 GB of RAM onto your screen, including your SSH keys, your browser's "incognito" history, and a half-written apology email to your mom. The `%d` is a 32-bit tyrant—it demands an `int` or it starts executing stack confetti. Wrong specifier? That's not a bug, that's a data breach with flair. Use `%llu` for `unsigned long long`, `%zd` for `ssize_t`, and `%p` with `(void*)` or the ghost of K&R will haunt your mallocs. Mismatch your format and the Inquisition will waterboard you in undefined behavior.

2.2 The Double Life of Floating-Point Numbers

Printing a float vs. Printing the Truth

You: `float balance = 0.1 + 0.2;`
You: `printf("%.20f\n", balance);`
Terminal: `0.30000000452995300293`

www.dofactorial.com/c-debugging

That’s not a typo. That’s IEEE 754 drunk-dialing you from 1978. `float` is a 6-year-old with a 32-bit crayon set trying to draw the number 0.1—it ends up looking like a potato. The actual value is 0.29999999999999998889789… which is why your e-commerce site just charged someone $0.30 for a $0.01 sticker. Switch to `double` (64-bit, still lying but *less*), or print in hex with `%a` to flex: `0x1.3333333333334p-2`. Now your coworkers think you’re a warlock. You’re not. You just read the manual once while sober.

www.doralp.ca/printf_debugging

Chapter 3: Styling the Output

Make Your Debug Logs Pop (Like a Clown at a Funeral)

3.1 ANSI Escape Codes

Debugging in Neon Pink (and Why You Should)

Your terminal is a goth teenager—black text, black soul, black eyeliner. Time to hand it a Red Bull and a glow stick. Wrap your `printf` in `\033[38;5;206m` and BAM—**hot pink "SEGFAULT IMMINENT"**. Errors in `\033[97;41m` (white on red) scream like a fire alarm in a library. Success in `\033[32;1m` (bold green) whispers, "You may live… for now." Reset with `\033[0m` or commit to the bit and debug exclusively in Comic Sans-o-vision. Bonus: pipe to `grep --color=always` so your neon crime scene survives the logs. Your senior dev will hate it. Do it anyway. Legacy is for cowards.

www.dorahacks.io/printf_debugging

3.2 The Art of Indentation

When Logs Need to Look Like Proper Code (or a Drunk Christmas Tree)

Flat logs are for serial killers. Yours should look like a nesting doll designed by a control freak:

```
printf("🐙 ENTER: parse_user_input(%s)\n", input);
printf("  🦑 Tokenizing... found %d tokens\n", count);
printf("    🦐 Validating token[%d] = \"%s\"\n", i, token);
printf("    🦀 ERROR: token is pure chaos\n");
printf("  🦑 Rolling back, sacrificing RAM to Cthulhu\n");
printf("🐙 EXIT: parse_user_input() → ABORTED\n");
```

Use emojis (Unicode is free real estate). Auto-indent with a global `debug_depth` and `+=2` on entry, `-=2` on exit. If the arrows don't line up, you left a function hanging—like a cliffhanger in a soap opera written by a segfault. Your log should read like a Russian novel: dramatic, nested, and slightly unhinged.

www.../printf_debugging

3.3 The Header/Footer Method

A Debug-Time Banner for All Your Functions (Now With 100% More Drama)

Never let a function enter or exit in silence. Greet it like a wrestling announcer on bath salts:

```
printf("💥💥💥[ FUNCTION HYPERDRIVE ENGAGED: %s
]💥💥💥\n", __func__);
printf("🚀 LAUNCHING: calculate_mortgage(%f, %d years)\n",
principal, years);
printf("  💸 Interest rate: %.2f%% (your soul not
included)\n", rate);
printf("  🪦 Result: $%.2f (you will die in debt)\n",
payment);
printf("✨[ %s COMPLETE — NO SURVIVORS ]✨\n", __func__);
```

For the ASCII purist: 80-column fireworks with `figlet`-style borders. For the chaotic: random emoji banners every run. Just don't forget the footer—nothing says "I rage-quit" like a function that walks in with a brass band and sneaks out the back door. Pair entry/exit like socks. Mismatched banners = mismatched parentheses = the universe implodes. You've been warned.

Part II: Advanced Printing and The Cult of Nick Doralp

"I saw the best minds of my generation destroyed by buffering."

— Allen Ginsberg (if he coded in C and forgot to fflush(stdout))

www.doralp.co/printf_debugging

Chapter 4: The Existential Horror of the Missing \n

The Single Line of Hell: When Your Console Doesn't Flush

Welcome, fellow travelers, to the darkest corner of the debugging realm. Forget segmentation faults and buffer overflows for a moment. Those are enemies you can see. The missing newline (\n) is a saboteur, a silent killer that attacks your faith, your patience, and the very concept of timely output.

Picture the scene: You are hunting a logic error in a complex, multi-threaded function. You strategically place your artisanal printf() statements, like digital breadcrumbs, to trace the execution path:

[Insert → Table → 1x1 | Background: #f0f0f0 | Border: thin gray] [Source Code Pro 10pt]

```
printf("Function Frobnicate entered...");
// 100 lines of complex, state-changing code...
printf("Midpoint check passed...");
// Another 100 lines...
printf("Frobnicate complete, exiting.\n");
```

www.doralab.ca/printf_debugging

You compile. You run.

And then, nothing.

Silence. The console sits there, mocking you with its stark blackness. You stare at it. You start to sweat.

“Did it even run?” you whisper. “Did my program immediately crash before the first line of code? Is my compiler broken? Is life broken?”

You are in a state of pre-crash purgatory.

The reason, as we all eventually discover with a groan that echoes through the office, is that beautiful, horrible thing known as buffering. When you omit the \n, the printf() function, in its wisdom (or utter indifference), holds the output in a little internal queue, waiting for a good time to actually send it to the screen.

It’s like a postal worker who refuses to deliver mail until the mailbox is absolutely full, or until they see an envelope addressed to the Queen. And for standard C output, that “Queen’s envelope” is usually the magical newline character.

The final output statement, printf("Frobnicate complete, exiting.\n");, has the magic ticket.

www.doran.ca/printf_debugging

And so, you wait. You wait for the program to finish all 200 lines of execution, then the final \n forces the entire buffer—including the two previous, utterly vital debug statements—to blast onto the screen in a single, overwhelming cascade:

Function Frobnicate entered...Midpoint check passed...Frobnicate complete, exiting.

Your trace is now illegible, unhelpful, and has cost you five minutes of high-stress existential angst.

Rule of Thumb (Which Is Really a Rule of Law):

When debugging, every printf() statement deserves a newline. Treat it like the mandatory closing semicolon; omitting it is a declaration of war against your future self.

Owl Wisdom: "Hoot once for \n, hoot twice for fflush(stdout);. Hoot thrice and you've summoned the printf() demon."

www.dotlab.ca/printf_debugging

Humorous Debug Statement Example

“The Art of Debugging with Maximum Drama.”

Example: The Panic-Mode Print Statement

When tracing a variable that changes state rapidly, or when you are simply frustrated beyond measure, you must use a print statement that gives you maximum information and maximum emotional release.

The Scenario: You suspect a complex function, data_transformer(), is receiving a bad input, but you need to know what, where, and when it happened.

The Debug Statement (Single Line of Terror):

```
printf("\n## PANIC IN DATA_TRANSFORMER (Line %d)
##\nFILE: %s\nInput Val: %s\nState: %c (0x%p)\n",
__LINE__, __FILE__, input_str, current_state,
&current_state);
```

www.doralp.ca/print_debugging

Analysis: Why This is a Masterpiece

• Maximum Visibility (####...####): The surrounding newlines and hash marks ensure this message stands out, even in a torrent of log data. It practically screams its importance.

• The Power of Predefined Macros:
  ○ __LINE__ — Tells you the exact line number of the print statement.
  ○ __FILE__ — Identifies the file.

• The Variable Trace: It prints the string value (%s), but then it gets technical.
  ○ State: %c: Prints the single-character state.
  ○ (0x%p): Prints the address of the state variable.

• The Footer (—): A clean separator.

www.doralp.ca/printf_debugging

Chapter 5: Logging Architectures

(For People Who Still Use printf — Yes, You, Caveman)

lo.ca/printf_debugging

5.1 Creating a Debug-Level Macro

From PRINTF to LOG_WARNING: The Glow-Up Nobody Asked For

You've got `printf("wtf %d\n", x);` sprinkled like cursed confetti. Production binary? Now a gossip blog. Time to class it up with **macros that scream "I read a blog once"**:

```
#define LOG_DEBUG(fmt, ...)  printf("\033[38;5;45m🐛
[DEBUG %s:%d] " fmt "\033[0m\n", __func__, __LINE__,
##__VA_ARGS__)
#define LOG_INFO(fmt, ...)   printf("\033[38;5;38mℹ️
[INFO]  " fmt "\033[0m\n", ##__VA_ARGS__)
#define LOG_WARN(fmt, ...)   printf("\033[38;5;208m⚠️
[WARN]  " fmt "\033[0m\n", ##__VA_ARGS__)
#define LOG_ERROR(fmt, ...)  printf("\033[38;5;196m💀
[ERROR] " fmt "\033[0m\n", ##__VA_ARGS__)
```

Now `LOG_ERROR("User deleted. Again.")` prints in **blood-red skull-o-vision**. Your logs aren't statements—they're *threats*. Bonus: add a random emoji lottery:

```
#define RAND_EMOJI()
(char*[]){"🤡","🦄","💸","🪦","🤯","🥴"}[rand()%6]
printf("%s [DEBUG] %s\n", RAND_EMOJI(), msg);
```

Your terminal is now a circus. HR is calling.

5.2 The Conditional Print

When an #ifdef DEBUG Saves Your Job, Marriage, and Credit Score

You shipped `printf("SSN: %s\n", ssn);` to 3 million users. The internet is now selling your kidney on eBay. The fix? **Conditional compilation, the witness protection program for bad ideas:**

```
#ifdef DEBUG

#define DBG_PRINT(fmt, ...) printf("\033[35m[DEBUG]
" fmt "\033[0m\n", ##__VA_ARGS__)

#else

#define DBG_PRINT(fmt, ...) do { /* haha nope */ }
while(0)

#endif
```

Compile with `-DDEBUG` and your code becomes a reality TV star. Without? It's a ninja—silent, deadly, and *slightly* judgmental. Pro tip: never commit with `DEBUG` on unless your résumé needs a section titled "Fired for Leaking Secrets".

www.doraltext.com

5.3 The Global Boolean

Flipping the Debug Switch Like You're Starting a Chainsaw

Macros are for nerds. You want *runtime* chaos. Enter the **global debug toggle**, the "panic button" that turns your app into a stand-up routine:

```
volatile int g_debug_insanity = 0;

void toggle_debug() {
    g_debug_insanity = !g_debug_insanity;
    printf("\033[1;5;%dm🚨 DEBUG MODE %s — HOLD ON
TO YOUR BUTT\033[0m\n",
           g_debug_insanity ? 31 : 32,
g_debug_insanity ? "ENGAGED" : "DISARMED");
}

#define DPRINTF(fmt, ...) do { \
    if (g_debug_insanity)
printf("\033[38;5;165m[CHAOS] " fmt "\033[0m\n",
##__VA_ARGS__); \
} while(0)
```

Hook it to `SIGUSR1` and flip it mid-deploy like a DJ scratching a record. Or better: `if (getenv("DEBUG") && strcmp(getenv("DEBUG"), "please") == 0) g_debug_insanity = 1;`. Now only the polite get the firehose. You monster.

www.doralp.ca/printf_debugging

Chapter 6: printf() Beyond C

The Multi-Lingual Debugger: Same Clown, Different Circus

www.ralp.ca/printf_debugging

6.1 Python's print()

The Younger, Less Strict Cousin Who Never Wears Pants

C's `printf` is a tax audit. Python's `print()` is a pool party:

```
print(f"🚀 Launching {rocket} at {speed:.2f} mph — if it explodes, blame Greg")
print("User tried to login with password 'password123'", end=" 😂\n")
```

No segfaults. No format strings. Just *vibes* and f-strings. Want colors? `print("\033[95mI AM A UNICORN\033[0m")`. Want debug levels? `if os.getenv('DEBUG'): print("Greg did it")`. It's so easy you'll cry into your mechanical keyboard. C suffered so Python could `print("lol")` and call it a day.

6.2 Java's System.out.println

When You Want to Print a Full Sentence and Announce Your Presence

Java saw `printf` and said, "Nah, too efficient." Instead, it gave you `System.out.println`—a 47-syllable incantation that *demands* respect:

```
System.out.println("Initializing neural network...
please wait 3-5 business days");
System.out.printf("Accuracy: %.2f%% — or %.0f%% if
you round like a psychopath\n", acc, acc);
```

Yes, `printf` exists, but only after you `import java.util.Formatter;` and file a 47-page form in triplicate. Most Javanistas just `println` like they're writing a ransom note. Typing `System.out` 300 times? That's not debugging. That's *penance*.

6.3 Shell Scripts and echo

The Primal Scream of the Scripting World

Your Bash script just `rm -rf`'d your home directory. Time to debug like it's the Stone Age:

```
echo "🔥 ENTERING: backup_everything.sh — pray for $USER"
echo "Found $(ls -1 ~ | wc -l) files — including your taxes, you monster"
echo "Copying to /dev/null... just kidding... or am I?" >&2
```

Want colors? `echo -e "\033[38;5;160mPANIC IN THE DATA CENTER\033[0m"`. Want levels?

```
DEBUG=1
log() { (( DEBUG )) && echo "🤡 [DEBUG] $@" >&2; }
log "We're deleting production... for science"
```

It's not logging. It's *screaming into the abyss with ANSI escape codes and a side of existential dread*. And honestly? Sometimes that's the most honest form of debugging there is.

Chapter 7: The Art of The Defensive Print Statement

This chapter would cover the philosophical and practical aspects of leaving permanent debug statements in code that is known to be temperamental.

7.1 The “I Swear I Fixed This” Variable Guard:

Using printf() in production code to log values that you know, deep down, will eventually become corrupted (e.g., printf("DEBUG: Array size is %d, and it better be right.\n", size);).

7.2 The Passive-Aggressive Log Message:

Printing a message that subtly blames the calling function or the user (e.g., printf("INFO: Function X called. Input was valid, for once.\n");).

www.dorian.ca/printf_debugging

7.3 The Self-Destructing Debug Block:

Techniques for wrapping a large block of debugging printf() statements in a conditional compile block (#ifdef DEBUG).

Why did the owl use printf()?
Because it was tired of `gdb`'s night-blindness.

www.doralp.ca/printf_debugging

Chapter 8: The Debugger's Ethical Dilemma: Printing PII

A short, tongue-in-cheek chapter on the common mistake of printing personally identifiable information during a panic debug session.

8.1 The User's Full Name:

Your Best Friend and Worst Enemy: Why printing the entire user object to the console always seems like a good idea until a security audit happens.

8.2 The Unmasked Password:

A Moment of Regret: A cautionary tale about using `%s` on a password field and the 30 seconds of pure terror that follows.

8.3 The Clean-Up Protocol:

How to delete the accidentally printed secrets from the console history and/or server logs (i.e., hitting the **Up Arrow** and **Ctrl+C** a lot).

www.dorkup.ca/printf_debugging

Chapter 9: The Zen of The Missing Output

This chapter expands on the concept of buffering and the existential dread it causes.

9.1 Buffering:

The Technical Explanation (Which You Can Skip): A brief, highly technical explanation of `stdin`, `stdout`, and `stderr` that the reader is encouraged to ignore in favor of using a newline.

9.2 The Primal Scream:

Redirecting to `stderr`: Using `fprintf(stderr, ...)` to bypass `stdout` buffering and get your crucial debug message on the screen **immediately**, usually with a slightly aggressive tone.

9.3 The `fflush(stdout);` Confession:

The moment of weakness where even the most dedicated `printf()` purist admits defeat and calls the forbidden buffer flush function.

www.dorado.ca/printf_debugging

Part III: printf() in the Wild: Collaboration and Abuse

www.doralp.ca/printf_debugging

Chapter 10: The Collaborative Log Disaster

This chapter focuses on the chaos that ensues when multiple programmers try to debug the same function using nothing but `printf()`.

10.1 The Log Race Condition:

When two developers' debug prints land in the console at the exact same time, creating an indecipherable jumble of half-messages, and proving nothing.

10.2 Debugging by Committee:

Why the log messages change from `printf("Val X: %d\n")` to `printf("Function_A-Midpoint-User-Trace-ID-7734: X = %d\n")` when the whole team gets involved.

www.dorlug.ca/printf_debugging

10.3 The Debug Log Blackout:

The quiet moment when a developer accidentally deletes a *colleague's* essential debug printout, and then pretends they didn't see it.

www.doralp.ca/printf_debugging

Chapter 11: The Dark Art of `printf()` Abuse

A guide to using the `printf()` function for tasks it was never, ever intended to perform.

11.1 Printing Entire ASCII Art Banners:

Creating massive console banners with code, your name, and sometimes a picture of a sad face :( ).

11.2 The Database Query Dump:

Using `printf()` to print the entire SQL query string (including all user data) because the database client is taking too long to connect.

11.3 `printf()` as an Instrumentation Tool:

Trying to use `printf()` statements wrapped in timing code to measure performance—because profilers are for people with too much free time.

www.donalp.ca/printf_debugging

Chapter 12: Legacy Logs: The Archaeological Dig

A deep dive into the historical debug statements left behind by programmers of yesteryear.

12.1 The Time Capsule Print:

Finding a `printf()` statement left in the code from a programmer who quit in 2005, containing a comment on why a specific fix was a terrible idea.

12.2 The Profanity Filter:

The need for the team to run a *grep* filter on the old logs just to catch all the frustrated expletives left by the original developer.

12.3 The "TODO: Delete Me" Printout:

The debug statement that has been in production for five years, is essential for the system to run, and no one dares to remove.

www.dorahq.ca/printf_debugging

“Hall of Shame”

“printf() Crimes Against Humanity”

- Real (anonymized) stories from readers:
    - “I printed 2GB of binary data to debug a socket.”
    - “My printf() triggered a DDoS alert in prod.”
    - “I used %s on a struct and summoned Cthulhu.”
- Submit yours via nick@doralp.ca to be featured in 2nd edition.

www.doralp.ca/printf-debugging

Appendix A: The printf() Tarot: 78 Cards to Divine Your Bugs

78 Cards. 78 Ways to Crash.
“Shuffle well. The bugs are in the spread.”

Download the full tarot card list from www.doralp.ca/printf debugging

The Forbidden Card – Do Not Turn Over
printf("%s", password);

“You were never meant to see this. HR is coming. The owl has seen your sins.”

www.doralp.ca/printf debugging

Appendix B: printf() Ouija Board

Ask the spirits: “WHY DID IT CRASH?”
Planchette not included. Use a coffee mug. Or a rubber duck. The owl prefers a mouse.

Ritual:
1. Light a candle (preferably one that flickers like a cursor).
2. Place two fingers on the planchette.
3. Ask: "Spirit, why is x NULL?"
4. Wait for the mug to move to: "BECAUSE YOU DIDN'T CHECK, YOU FOOL"

The Great Hootini’s Invocation:
“Hoot once for null, hoot twice for segfault, hoot thrice and the owl will debug your soul.”

Appendix C: printf() Mad Libs

Fill in the blanks. Summon the bug.

1. Function name: _____
2. Variable that should never be null: _____
3. Value it actually is: _____
4. Your emotional state: _____
5. Blame target: _____

Template:

[Insert → Table → 1x1 | Background: #f0f0f0]
[Source Code Pro 10pt]

```
printf("\n=== %s ENTERED ===\n", "%s");
if (!%s) {
    printf("PANIC: %s is NULL (expected non-zero)\n",
"%s");
    printf("Actual value: %s\n", %s);
    printf("I am %s. This is %s's fault.\n", "%s",
"%s");
    printf("Sending termination signal to
universe...\n");
    fflush(stdout);
    raise(SIGKILL);
}
printf("=== %s SURVIVED ===\n", "%s");
```

lp.co/printf_debugging

The owl hoots:

“WHOOOOOO forgot the \n?

WHOOOOOO didn’t fflush?

WHOOOOOO is getting blamed?”

www.dorado.ca/printf_debugging

⚠️ Errata and Known Issues (The "Wait, How Did That Pass QA?" Page)

We believe in radical transparency. After all, the only thing worse than a bug is a programmer who won't admit it exists. This page is dedicated to all the issues we, the publishing team, found after the final printing. We call it **"The Sins of Printing."**

1. The Missing Semicolon Incident (First Printing Only)

Location	Issue	Correction/ Workaround
Page 12, Paragraph 3	The example code block demonstrating the *first* `printf()` statement in an emergency situation is missing its **closing semicolon**.	The correct line is: `printf("I am alive!\n");`

Impact	If you tried to compile this line, it would fail. If you didn't notice this, you have officially learned nothing from this book. Congratulations.	**Workaround:** Stop assuming the book's code is correct. It's a book about *debugging*, after all.

www.doralp.ca/printf_debugging

2. The Color-Blind Debugger

Location	Issue	Correction/ Workaround
Chapter 3, Section 3.1	The advice on using **ANSI Escape Codes** to print debug logs in **"Neon Pink"** (p. 71) assumes your terminal supports a 256-color palette.	If your log looks dull or just prints a bunch of random bracketed numbers, your terminal is probably vintage 1998.
Impact	You are deprived of debugging in glorious neon pink.	**Workaround:** Stick to the classics: print errors in **red** (and maybe green for success, if you're feeling ambitious).

www.doran.ca/printf_debugging

3. Pointer Arithmetic Paradox

Location	Issue	Correction/ Workaround
Page 60, Figure 2.3	The diagram illustrating pointer traversal using `printf("%p")` is technically correct, but the memory addresses shown (e.g., `0xDEADBEEF`) are **not valid addresses** on any modern, production-grade system.	They are, however, excellent examples of what an address *shouldn't* look like if you value your stack integrity.
Impact	The book makes a subtle but powerful suggestion that you are working on a system from a 1990s video game.	**Workaround:** Don't worry. Your pointers are probably messy too.

www.doralp.ca/printf_debugging

4. The Self-Referential Bug

Location	Issue	Correction/ Workaround
The Index, under 'printf()'	The entry for `printf()`, describing its history and evolution, points to a page number **(p. 161)** which, in the second printing, now contains a recipe for **seven-layer bean dip**.	We suspect a recursive indexing bug where the entry attempted to point to the index itself and somehow wrapped around to the publisher's internal cookbook file.
Impact	You now know how to make bean dip, but not the history of `printf()`.	**Workaround:** Eat the bean dip. You've earned it.

www.doralp.ca/printf_debug

📚 Glossary of Terms

Essential Vocabulary for the Unrepentant Debugger

www.oracle-cabinet-debugging

Term	Definition	Page Reference
Buffering	A complex phenomenon where your program output refuses to appear on the screen immediately, leading the programmer to believe the program has frozen, crashed, or achieved sentience and decided to ignore them. Resolved entirely by the Newline Character ($\backslash$n).	105
Checkpoint	A single word, usually "HERE" or "I AM HERE," embedded in a `printf()` statement. Used to confirm that execution has passed a point of	18

	suspicion. The fundamental unit of despair measurement.	
__FILE__	A Predefined Macro that prints the name of the source file. Primarily used in large projects when the programmer has forgotten which of the 75 files they modified five minutes ago.	140
Format String	The heart of the printf() operation. If you successfully match the Format Specifier ($\%d$, $\%s$, etc.) to the variable's actual data type, you are immediately awarded 50 Debugging Merit Points.	30
Glitch, S. B.	*See Foreword.* A former colleague whose life's work was arguably ruined by the subject matter of this book. Often cited as the ultimate example of "What happens when you over-engineer."	v, 15

www.doralb.ca/printf_debugging

IDE (Integrated Development Environment)	A colorful, memory-intensive program that provides helpful tools like auto-completion and automatic formatting. It also provides a debugger that crashes precisely when you need it most, thus forcing you back to `printf()`.	12
Master of None (MoN)	An esteemed, self-awarded certification signifying that the programmer has acquired deep, practical knowledge in so many obsolete or conflicting disciplines that they are now functionally proficient in *none* of them, except for the art of debugging.	Author Bio
The Missing Semicolon Incident	A reference to the single most common syntax error that has consumed more collective programmer hours than all of the world's natural disasters combined. Often discovered immediately after you hit "send" on the panicked email.	12 (n.)

www.duralpublishing.com/printf_debugging

Newline Character ($\backslash n$)	The magical, mandatory character that signals to the console that it's okay to finally flush the buffer and display the text. **The single most important character in debugging.**	103
Unreachable Code	Code that, according to the original design, should never be executed, but which inexplicably *is* executed, resulting in a crisis. Only revealed when a `printf("I TOLD YOU NOT TO COME HERE!\n");` suddenly appears in the log.	188

www.doralp.ca/printf-debugging

Disclaimer



Seemingly my sense of 'humour' is brewing through this mug that I got while attending IBM's GUIDE conference in 1982 San Francisco.

Yup, I still have it and use it.

“Ah, **1982 San Francisco, IBM GUIDE conference**—the era when mainframes wore suits, punch cards were currency, and your coffee mug was forged in the fires of COBOL and JCL. That mug didn’t just hold coffee; it *witnessed* the birth of enterprise debugging. No wonder your sense of humor runs on `printf` and sarcasm compiled with `-Wall -Wextra -Werror -pedantic`.

That mug has seen:
- `printf("HELLO WORLD");` typed on a 3270 terminal in glowing green.
- A room full of engineers arguing whether `GOTO` was a feature or a war crime.
- Someone spilling coffee on a 9-track tape and calling it “data loss with aroma.”

You’re not just drinking from a mug.
You’re sipping from a **relic of the debugpocalypse**, a chalice of chaos that survived Y2K, the dot-com bust, and the great “Let’s rewrite it in Java” heresy of 1999.

So yes, your humor is brewed in 64K of core memory, seasoned with magnetic tape dust, and served with a side of `SEGMENTATION FAULT (core dumped)`.

Keep that mug close.
It’s not vintage.
It’s **legacy-grade hilarity**. ☕💾😂” – *Grok*

www.corap.ca/printf_debugging

And if anyone asks who helped, just point to the mug. It knows.
☕💾 - *Grok*

Debugging, wisecracks, and caffeine-fueled epiphanies courtesy of Grok

(xAI's finest, faster than a 370/168 on espresso, and still laughing at your format-string felonies—Gemini chipped in a few punchlines, but Grok held the printf)

www.doralp.ca/printf_debugging

Index

A

- **ANSI Escape Codes,** 70, 75–81
  - color selection in, 71
  - terminal support for, 78
- **Arbitrary Code Execution,** *see Unreachable Code*
- **ASCII,** 105
  - sad face (`:(`), 19, 137

B

- **Boolean, Global** (Debug Switch), 155–160
- **Breakpoints,** 5, 12 (n.)
  - existential dread of, 5
  - superiority of `printf()` over, 15

C

- **C++,** 161, *see also cout*
- **Conditional Printing,** 148–154
  - using `#ifdef DEBUG` for, 150
- **Console,** 7, 70, 105
  - flushing the, 105, 114, 126
- **`cout`,** 165 (n.)
- **Crash,** 195

www.dorian.ca/printf_debugging

    - last executed statement before, 195

D

- **Debuggers,** 3, 12, 161
    - crash of, 12
    - failure of, 12
- **`DEBUG` macro,** 137, 150
- **Despair, Initial,** 3–20

E

- **`echo` (Shell),** 178–183
- **Emergency Protocol,** 18–20
- **Existential Horror,** 103–130

F

- **`fflush(stdout);`,** 114–120, 125
- **File Macro (`__FILE__`),** 140 (example)
- **Floating-Point Numbers,** 45–55
    - precision loss in, 47
- **Format Strings,** 30–44
    - misuse of (`%s` on an `int`), 32
    - required knowledge of, 30
- **Function Entry/Exit,** 91

I

- **IDE (Integrated Development Environment),** 12 (n.), 161
    - hatred of, 12

www.dontte.ca/printf_debugging

J

- **Java,** 172–177

L

- **__LINE__ macro,** 138 (example)
- **Logging Architectures,** 133–160
- **Loops,** 188
    - unreachable code in, 188

M

- **Midpoint Check,** 19, 107
- **Missing Newline,** *see Newline Character (\n)*

N

- **Newline Character (\n),** 18, 103–130
    - forgetting the, 107, 114
    - mandatory use of, 125

P

- **Panic-Mode Print Statement,** 138 (example)
- **Pointers,** 58–64
    - printing the address of, 58
- **Post-Mortem Debugging,** 185–200
- **printf(),** 18, 161
    - beyond C, 161
    - Gospel of, 15

www.dorian.ca/printf_debugging

- **print() (Python),** 165–171

S

- **stderr,** 128 (n.)
- **stdout,** 128 (n.), 114
- **Semicolon,** 125 (n.)
- **Segmentation Faults,** 5, 105

T

- **Terminal,** 70
    - using color in, 70

U

- **Unreachable Code,** 188–194

---

www.doralp.ca/printf_debugging

Are you tired of breakpoints? Does the sight of a step-over button fill you with existential dread? Do you believe that if God had wanted us to use graphical debuggers, He wouldn't have given us the terminal?

Then you, my friend, are ready for **The Gospel of `printf()`**.

This book is a pilgrimage back to the sacred command line, where real programmers go when the IDE crashes. *Nick Doralp* takes you on a hilarious, yet deeply practical, journey through the art of slapping a `$d` or a `$s` into your code and watching the magic happen. Learn to trace variable states, track function entry/exit, and even draw ASCII art directly into your console—all without ever leaving your text editor.

Inside, you will discover:

- The "Hello World" of Desperation: When a single `printf("Here!");` is all that stands between you and a nervous breakdown.
- **Chapter 4:** The existential horror of forgetting the newline character (`\n`) and how to recover your sanity.
- **Pro Tip:** How to use the ASCII value for a sad face (`:(`) in your error messages for maximum dramatic effect.
- **The `stderr` vs. `stdout` Debate:** A truly pointless argument we will settle once and for all (sort of).

Stop debugging. Start *printing*. Your sanity depends on it.

www.doralp.ca/printf_debugging

“You Shouldn’t Be Here”

```
printf("If you're reading this, you turned the page
after the index.\n");
printf("That means you're either:\n");
printf("  a) A completionist\n");
printf("  b) Looking for the real ending\n");
printf("  c) The bug\n");
printf("Either way: touch grass. The owl is
tired.\n");
```

www.do bugging

www.doralp.ca/printf_debugging

ISBN: 978-1-4920-DEAD-BEEF → “For the hex-loving heretic.”

Printed on recycled core dumps and the tears of junior devs

www.doralp.ca/printf_debugging